

VM704

4 Channel Color Multiplexer

Features:

- Real time & high resolution
- Window displays: single full screen, auto sequential, 4-channel display
- System auto detection
- Adjustable video on channels
- Video loss indication
- Freeze feature
- VCR play zoom back
- Alarm I/O
- On screen display



Specifications:

Model	VM704
Refresh Rate	30 fps (NTSC), 25 fps (PAL)
Resolution (H X V)	720 x 480 (NTSC); 720 x 576 (PAL)
Freeze	Yes
VCR Zoom Back	Yes
Video Input Port	4+1 (VCR) camera
Video Output Port	1 switch & 1 quad output
Video Color	16 million true color
Alarm Input	4
Alarm Output	1
Alarm Duration	1 - 99 sec.
Camera Title	10 Characters
Time /Date set	Built-in real time clock
Dwell Time	1 – 30 sec.
RS - 232 Port	Yes
Load Impedance	75 ?
Operating Environment	10 – 80% RH, 0 - 50 °C
Power Source	DC 12V +/-10%, 500mA
Power Consumption	6W maximum
Dimension (mm)	240 (W) x 44.4 (H) x 151 (D)
Weight	1.3 Kg

Packaging:

- 4 Channel multiplexer
- Manual

Specifications are subject change due to availability.
Parts may be replaced with similar or better quality/grade.

Update: Apr. 2, 2005